



**RFQ NUMBER** : 2012305254

**DATE** : 07.12.2023 **REQ No** : 1012305261

**REQ TITLE** : Supply of valves for firefigh

**DELIVERY LOCATION**: 0018 - LII STORE

**CLOSING DATE** : 13.12.2023

CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
1	3600060479		VALVE;ISOLATION GATE VALVE FOR FIREFIGHTING DN 65; MANUFACTURER: M/S.KENNEDY VALVES, TYPE: RESILIENT SEATED CAST IRON GATE VALVES T O AWWA C509; SIZES: 150MM FLANGED; WORKING PRESSURE: 250 PSIG (17.20 BAR);MODEL-4068: OS&Y GATE VALVES, FLANGED; FLANGE FACE IN R F / FF; FACE TOFACE ANSI B 16.10; OPERATION-OPERATING NUT, HAND WHEEL; TEST PRESSURE-SEAT TEST: 400 PSI (27 BAR) BODY HYDRAULIC: 50 0 PSI (34 BAR);COATING-FUSION BONDED NONTOXIC EPOXY COATING NSF 61 CERTI_ED MEETINGAWWA C-550 STANDARDS; UL/FM APPROVED; STANDA RD C OLOR: RED; FOR L DESALFIREFIGHTING SYSTEM.	5	EA				
2	3700026339		VALVE_GATE; TYPE: RESILIENT SEATED WEDGE, ISOLATION; SIZE: 150MM; CONNECTION: RF/FF FLANGED; DESIGN RATING: 250PSIG; OPERATED: HANDW HEEL; BODY MATERIAL: CI ASTM A126 CLASS B; FACE TO FACE LENGTH: 267MM; STEMDESIGN: OUTSIDE SCREW AND YOKE; TRIM: BRZ STEM,	5	EA				





**RFQ NUMBER** : 2012305254

**DATE** : 07.12.2023 **REQ No** : 1012305261

**REQ TITLE** : Supply of valves for firefigh

**DELIVERY LOCATION**: 0018 - LII STORE

**CLOSING DATE** : 13.12.2023

CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			STEM NUT , DI PACKINGGLAND; SOFTGOODS: NBR O-RING; STANDARD: ANSI B16.10, AWWA C509, AWWAC550, FM, UL; MFR: KENNEDY VALVE CO: MPN: 4068: AD DI TIONAL INFO: TESTPRESSURE RATING: 400PSI (27BAR) SEAT; 500PSI (34BAR); COATING-FUSIONBONDED NONTOXIC EPOXY COATING NSF 61 CERTIF IED MEETING; OPERATING NUT;BODY HYD; APPLICATION: FIREFIGHTING						
3	4000005487		VALVE BUTTERFLY, SIZE: NB80, KV MODEL: 3" W300 & 300 PSI, FLANGE SIZE:80 MM, TYPE: WAFER WITH SUPERVISORY TAMPER SWITCH, CONNECTION DETAIL:BETWEEN FLANGED TO ANSI B 16.5, # 150, MATERIAL: BODY COATING: FUSIONBONDED NYLON 11, UPPER & LOWER SHAFT: STAINLESS STEE L 416, DISC SBR,APPROVAL: UL LISTED, FM APPROVED, VALVE APPLICATION FIRE FIGHTINGSYSTEM OF RATED PR. 12 BAR AT L-DESAL MMD, MAN UF ACTURER: KENNEDY VALVE(USA)		EA				





**RFQ NUMBER** : 2012305254

**DATE** : 07.12.2023 **REQ No** : 1012305261

**REQ TITLE** : Supply of valves for firefigh

**DELIVERY LOCATION**: 0018 - LII STORE

**CLOSING DATE** : 13.12.2023

CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
4	4000005489		VALVE BUTTERFLY, SIZE: NB150, KV MODEL: 6" W300 & 300 PSI, FLANGE SIZE:150 MM, TYPE: WAFER WITH SUPERVISORY TAMPER SWITCH, CONNECTI ON DETAIL: BETWEEN FLANGED TO ANSI B 16.5, # 150, MATERIAL: BODY COATING: FUSIONBONDED NYLON 11, UPPER & LOWER SHAFT: STAINLESS ST E EL 416, DISC SBR,APPROVAL: UL LISTED, FM APPROVED, VALVE APPLICATION FIRE FIGHTINGSYSTEM OF RATED PR. 12 BAR AT L-DESAL MMD, M AN UFACTURER: KENNEDY VALVE(USA)	2	EA				
5	3700026340		VALVE_GATE; TYPE: RESILIENT SEATED WEDGE, ISOLATION; SIZE: 200MM; CONNECTION: RF/FF FLANGED; DESIGN RATING: 250PSIG; OPERATED: HANDW HEEL; BODY MATERIAL: CI ASTM A126 CLASS B; FACE TO FACE LENGTH: 292MM; STEMDESIGN: OUTSIDE SCREW AND YOKE; TRIM: BRZ STEM, STEM NUT, DI PACKINGGLAND; SOFTGOODS: NBR O-RING; STANDARD: ANSI B16.10, AWWA C509, AWWAC550,	1	EA				





**RFQ NUMBER** : 2012305254

**DATE** : 07.12.2023

**REQ No** : 1012305261

**REQ TITLE** : Supply of valves for firefigh

**DELIVERY LOCATION**: 0018 - LII STORE

**CLOSING DATE** : 13.12.2023

CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			FM, UL; MFR: KENNEDY VALVE CO: MPN: 4068: AD						
			DI						
			TIONAL INFO: TESTPRESSURE RATING: 400PSI						
			(27BAR) SEAT; 500PSI (34BAR);						
			COATING-FUSIONBONDED NONTOXIC EPOXY						
			COATING NSF 61 CERTIF IED						
			MEETING; OPERATING NUT;BODY HYD						

TOTAL AMOUNT IN WORDS:

TOTAL AMOUNT:

#### **SPECIAL NOTES / INSTRUCTIONS:**

Supply of valves for firefighting system in L-Station Desal.

For any further enquiry cont. Dipesh Kumar Chauhan off/ No. 04-8140603,

M/ No. 0522456862, E-mail-dipesh.chauhan@dewa.gov.ae

#### **STANDARD TERMS & CONDITIONS**

- 1) Prices should be 'DDP' delivery duty paid at DEWA stores.
- 2) Quotation to be submitted only in local currency U.A.E Dirhams
- 3) DEWA Standard payment terms is '30 days credit' from the date of acceptance of material





**RFQ NUMBER** : 2012305254

**DATE** : 07.12.2023 **REQ No** : 1012305261

**REQ TITLE** : Supply of valves for firefigh

**DELIVERY LOCATION**: 0018 - LII STORE

**CLOSING DATE** : 13.12.2023

CLOSING TIME : 10:00:00

4) No DEWA staff or his or her relatives up to third degree should have ownership or partnership in your company, and your participation in DEWA tenders / RFQs should not constitute a Conflict or perceived Conflict of Interest.

5) The offered product and/ or services in the Quotation, shall be conforming and in accordance with DEWA Energy Management Policy & EnMS Manual.

**SUPPLIER'S REMARKS:** 

SUPPLIER'S SIGNATURE AND STAMP