

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2012505860
DATE : 19.11.2025
REQ No : 1012506185
REQ TITLE : SPARES 1012506185
DELIVERY LOCATION : 0014 - G STORES, JAPS
CLOSING DATE : 26.11.2025
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
1	2700085013		TRANSMITTER_LIQUID LEVEL; INPUT RANGE: -1000 TO 1000IN H2O; OUTPUTRANGE: 4 TO 20MA; SUPPLY RATING: 24VDC; SIZE/CONNECTION: 2IN FLAN GED;MATERIAL: PU PAINTED AL; CALIBRATION RANGE: 0 TO 19000MM WC; FILL:SILICONE OIL; CONNECTION MATERIAL: 316L SS; ENCLOSURE: NEMA 4X , IP66/68;MOUNT: FLUSH; MFR: ROSEMOUNT INC: MPN: 3051L3AG0XD21ABL5M5Q4C1DFF1:ADDITIONAL INFO: TYPE: ELECTRONIC; 2-WIRE; SMART; A CCU RACY: $\pm 0.075\%$ OF SPAN; CONDUIT ENTRY SIZE: M20 X 1.5; COMMUNICATION PROTOCOL: HART;CABLE ENTRY: M20; DISPLAY: LCD; MEASUREMENT TYP E: DIFFERENTIALPRESSURE; MEASURING RANGE: 0 TO 19M; ISOLATING DIAPHRAGM/WETTED PARTSMATERIAL: 316L SS; PROCESS CONNECTION (SIZ E/RAT ING): 2IN ANSI B16.5;150# (HIGH SIDE); 1/2IN NPTF (LOW SIDE); CAPILLARY MATERIAL AND LENGTH:DIRECT CONNECTION; NO CAPILLARY;	2	EA				

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2012505860
DATE : 19.11.2025
REQ No : 1012506185
REQ TITLE : SPARES 1012506185
DELIVERY LOCATION : 0014 - G STORES, JAPS
CLOSING DATE : 26.11.2025
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			LIT-01G CL10CL011A; MOUNTING FLANGESIZE/RATING/MATERIAL (HIGH SIDE): 2IN/ANSI/ASME B16.5 CLASS 150/SS;PROCESS FILL (HIGH PRESSURE S IDE): SI LICONE 200; SPECIFIC GRAVITY:0.93; TEMPERATURE LIMITS: -45 TO 205DEG C; CONFIGURATION: DIFFERENTIAL;FLANGE ADAPTER: SS; O- RING: GLA SS FILLED PTFE; BOLTING MATERIAL: ASTM A193; GR. B7M BOLTS; W/CALIBRATION CERTIFICATE; W/CUSTOM SOFTWARECONFIGURATION; LO WER HOUSIN G FLUSHING CONNECTION RING MATERIAL/SIZE:316 SS/1/4IN-18 NPT						
2	2700085015		TRANSMITTER_LIQUID LEVEL; INPUT RANGE: -250 TO 250IN H2O; OUTPUT RANGE:4 TO 20MA; SUPPLY RATING: 24VDC; SIZE/CONNECTION: 2IN FLANGE D;MATERIAL: PU PAINTED AL; CALIBRATION RANGE: 65 TO 3380MM WC; FILL:SILICONE OIL; CONNECTION MATERIAL: 316L SS; ENCLOSURE: NEMA 4X , IP66/68; MOUNT: FLUSH; MFR: ROSEMOUNT INC:	2	EA				

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2012505860
DATE : 19.11.2025
REQ No : 1012506185
REQ TITLE : SPARES 1012506185
DELIVERY LOCATION : 0014 - G STORES, JAPS
CLOSING DATE : 26.11.2025
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			MPN:3051L2AG0XD21ABL5M5Q4C1DFF1: ADDITIONAL INFO: TYPE: ELECTRONIC; 2-WIRE;SMART; ACC URA CY: $\pm 0.075\%$ OF SPAN; CONDUIT ENTRY SIZE: M20 X 1.5;COMMUNICATION PROTOCOL: HART; CABLE ENTRY: M20; DISPLAY: LCD;MEASUREMENT T YPE: DIFFERENTIAL PRESSURE; MEASURING RANGE: 0 TO 2600MM;ZERO SUPPRESSION/ELEVATION: SUPPRESSION 65MM WC; PROCESS FLUID: 30%NAOH; COVER FLANGE BODY MATERIAL; NON-WETTED PARTS: 316 SS; ISOLATINGDIAPHRAGM AND WETTED PARTS MATERIAL: REFER DIAPHRAGM SEAL PORTION; PROCESS CONNECTION (SIZE/RATING): 2 IN ANSI B 16.5; 150# (HIGH SIDE);1/2IN NPTF (LOW SIDE); DIAPHRAGM/WETTED PARTS MATERIAL: 316L SS ;CAPILL ARY MATERIAL AND LENGTH: DIRECT CONNECTION; NO CAPILLARY;LIT-01GCN20CL001B; MOUNTING FLANGE SIZE/RATING/MATERIAL (HIGH SIDE):2IN/AN SI/ASME B16.5 CLASS 150/SS; PROCESS FILL (HIGH						

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2012505860
DATE : 19.11.2025
REQ No : 1012506185
REQ TITLE : SPARES 1012506185
DELIVERY LOCATION : 0014 - G STORES, JAPS
CLOSING DATE : 26.11.2025
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			PRESSURE SIDE);SILICONE 200; SPECIFIC GRAVITY: 0.93; TEMPERATURE LIMITS: -4 5 TO 205D EGC; CONFIGURATION: DIFFERENTIAL; FLANGE ADAPTER: SS; O-RING: GLASS FILLEDPTFE; BOLTING MATERIAL: ASTM A 193; GR. B7M BOL TS; W/CALI BRATIONCERTIFICATE; W/CUSTOM SOFTWARE CONFIGURATION; LOWER HOUSING FLUSHINGCONNECTION RING MATERIAL/SIZE: 316 SS/1/4IN-1 8 NPT						
3	2700085030		DETECTOR_RESISTANCE TEMPERATURE; TEMPERATURE RATING: 0 TO 100DEG C;RESISTANCE: 100OHM; ELEMENT MATERIAL: PT; WIRE: 3; CONNECTION: 1 -1/2INANSI B16.5 150LB RF FLANGED; INSERTION LENGTH: 500MM; SHEATH SIZE: 6MMDIA; SHEATH MATERIAL: 316L SS; MFR: EMERSON ELECTRIC C O : MPN:0065-1-0-5-F-0110-D-0500: MFR: ROSEMOUNT INC: MPN:0600-F10-A1-Q8-R01-XA: ADDITIONAL INFO: CABLE SIZE: M20 X 1.5;CONSTRUCTI ON: DRILLED BAR STOCK; DISPLAY: LCD; ENCLOSURE: IP66/68;ELEMENT CONNECTION: 1/2IN NPTF; ELEMENT LENGTH: TO SUIT THERMO WELL	2	EA				

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2012505860
DATE : 19.11.2025
REQ No : 1012506185
REQ TITLE : SPARES 1012506185
DELIVERY LOCATION : 0014 - G STORES, JAPS
CLOSING DATE : 26.11.2025
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			ULENGT H; T HERMO WELL TYPE: TAPERED PATTERN; UNION NIPPLE MATERIAL: SS;WETTED PARTS MATERIAL: 316L SS; STYLE: DIN; WELL SIZE: 7MM ID; 26.5 MMOD ; TE/TIT-01GCK28CT001; SPRING LOADED MECHANISM REQUIRED; W/O THERMOWELL						
4	2700138716		SWITCH_LEVEL; ELECTRICAL RATING: 250VAC, 24VDC 1A; SPDT; ENCLOSURE: NEMA4X/7/9 WITH JUNCTION BOX; TEMPERATURE RATING: -40 TO 80DEG C ; MFR: ORIONINSTRUMENTS/AMETEK: MPN: ORS-300.	3	EA				
5	2700085024		TRANSMITTER_CONDUCTIVITY; INPUT RANGE: 0 TO 20000US/CM; OUTPUT RANGE: 4TO 20MA; SUPPLY RATING: 24VDC; TYPE: 2-WIRE, CONTACTING; ACC URACY: +/-0.7%, +/-0.002US/CM; TEMPERATURE RANGE: 0 TO 50DEG C; MATERIAL: ABS;ENCLOSURE: NEMA 4, 4X, IP65; MFR: ROSEMOUNT INC: MPN: XMT-C-HT-11-60:ADDITIONAL INFO: CABLE ENTRY: M20; COMMUNICATION PROTOCOL: HART;ACCESSORIES: 2IN PIPE/SURFACE	4	EA				

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2012505860
DATE : 19.11.2025
REQ No : 1012506185
REQ TITLE : SPARES 1012506185
DELIVERY LOCATION : 0014 - G STORES, JAPS
CLOSING DATE : 26.11.2025
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			MOUNTING BRACKET; LO CA L INDICATION: LCD;SMART; W/MOUNTING BRACKET; 23820-00; GLAND FITTING; 23554-00; QIT;01GCK28CQ001A; ANALYZERS						
6	2700128138		SWITCH_FLOW; SIZE/CONNECTION: 22MM; ELECTRICAL RATING: 240V AC AND 120VDC 0.6A MAX; MAX OPERATING PRESSURE: 10 BAR, CONTACT: NO WIT H NO FLOW;CABLE: 25CM PVC INSULATED, MATERIAL: ACETAL RESIN; MFR: SENSATATECHNOLOGIES: MPN: FS22LF, MODEL: CYNERGY3, FLOW SETPOINT : 1.75 L/MINOPERATE, 0.75 L/MIN RELEASE	2	EA				

TOTAL AMOUNT IN WORDS:

TOTAL AMOUNT:

SPECIAL NOTES / INSTRUCTIONS:

SPARES FOR NDM PLANT AT G STATION JEBEL ALI.

INSTALLED QTY/ STOCK

ITEM 1-3: 2/0

MATERIAL AND OR SERVICE PROVIDED TO DEWA SHOULD PREFERABLY BE ENERGY EFFICIENT AND ENVIRONMENT FRIENDLY.

Page6 of 8

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2012505860
DATE : 19.11.2025
REQ No : 1012506185
REQ TITLE : SPARES 1012506185
DELIVERY LOCATION : 0014 - G STORES, JAPS
CLOSING DATE : 26.11.2025
CLOSING TIME : 10:00:00

ITEM 4: 4/0
ITEM 5: 10/0
ITEM 6: 4/2
ITEM 7: 31/4

PREVIOUS PURCHASE DETAILS:

ITEM 3: 3011703142 M/s. TRIZAC ABU DHABI
ITEM 6: 3012303798 M/s. PROJECT SOLUTIONS COMPANIES
ITEM 7: 3012103176 M/s. GEN.TECH.SERVICES L.L.C.
REMAINING ITEMS FIRST TIME PROCUREMENT.

WARRANTY 1 YEAR.

STANDARD TERMS & CONDITIONS

- 1) Prices should be 'DDP' delivery duty paid at DEWA stores.
- 2) Quotation to be submitted only in local currency U.A.E Dirhams
- 3) DEWA Standard payment terms is '30 days credit' from the date of acceptance of material
- 4) No DEWA staff or his or her relatives up to third degree should have ownership or partnership in your company, and your participation in DEWA tenders / RFQs should not constitute a Conflict or

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2012505860
DATE : 19.11.2025
REQ No : 1012506185
REQ TITLE : SPARES 1012506185
DELIVERY LOCATION : 0014 - G STORES, JAPS
CLOSING DATE : 26.11.2025
CLOSING TIME : 10:00:00

perceived Conflict of Interest.

5) The offered product and/ or services in the Quotation, shall be conforming and in accordance with DEWA Energy Management Policy & EnMS Manual.

6) Confidentiality Clause: The Supplier/Service Provider shall treat all information and data (excluding open data) contained in the Purchase Order or obtained by the Supplier/Service Provider in connection with the execution of Works as proprietary and strictly confidential. In particular, the Supplier/ Service Provider shall not publish or disclose any data or information including but not limited to personally identifiable information, government data, project details, specifications, drawings or photographs concerning the Works to any third parties without the prior written consent of the Employer.

If the Supplier/Service Provider is obligated to obtain NOCs / Permits /Permissions for the Project from Government agencies as per the terms and scope of the Contract, the Supplier/Service Provider shall submit only the specific data required for the purpose to the authorized team of the agency, through their prescribed channel / system, subject to information security requirements

The Supplier/Service Provider shall comply with all the applicable data protection laws and regulations.

SUPPLIER'S REMARKS :

SUPPLIER'S SIGNATURE AND STAMP