

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2492400059
DATE : 16.01.2024
REQ No : 1172300832
REQ TITLE : Power supply unit 1172300832
DELIVERY LOCATION : 0014 - G STORE SPAR&CHE
CLOSING DATE : 22.01.2024
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
1	7000000013		POWER SUPPLY UNIT AC TO DC CONVERTER INPUT 230 VAC, OUTPUT VOLTAGE LEVEL DC FROM 24 V TO 220 V DC, WATT- 3500 AT OUTPUT WITH FOLLOW ING FEATURES : 1. HIGH EFFICIENCY. 2. FORCED AIR COOLING BY BUILT IN DC FAN AND TEMPERATURE CONTROLLED FANS. 3. PROTECTIONS : SHORT CIRCU IT / OVERLOAD / OVER VOLTAGE / OVER TEMPERATURE. OF REPUTED MAKE , PROVIDED WITH 1 YEAR VALID CALIBRATION CERTIFICATE AND 2 YEARS WARR ANTY AGAINST ANY MANUFACTURING DEFECTS.	1	EA				
2	7000000013		PORTABLE BATTERY CHARGER - 25 AMPS 6V -120 VOLTS. 1. THE CHARGER SHALL BE MOBILE (WITH WHEELS AND STOPPER) AND DIGITAL WITH BUILT IN AM METER AND VOLTMETERS FOR MEASURING AC, DC CURRENTS AND VOLTAGES WHICH CAN BE USED DURING BATTERY CHARGING. THE CHARGER SHALL BE BUIL T TO ABSORB SHOCKS DURING THE MOVEMENT FROM ONE PLACE TO OTHER. THE CHARGER SHALL	3	EA				

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2492400059
DATE : 16.01.2024
REQ No : 1172300832
REQ TITLE : Power supply unit 1172300832
DELIVERY LOCATION : 0014 - G STORE SPAR&CHE
CLOSING DATE : 22.01.2024
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			BE CAPABLE OF APPLYING HIGHER VOLTAGE FOR SEVERAL HOURS TO SPEED UP BATTERY CHARGING IN BOOST. 2. INPUT: A) INPUT SUPPLY : AC 380V + 10% , 3 PHASE, 50HZ + 5%, WITH SOFT STARTING FACILITY B) OVERLOAD AND SHORT CIRCUIT PROTECTION AT INPUT OF THE BATTERY CHARGER: CIRCUIT BREAKER (3 POLE) C) SURGE SUPPRESSOR IN 3PHASE AC INPUT MAINS CIRCUIT FOR THE PROTECTION AGAINST VOLTAGE SURGES. 3. OUTPUT: A) NOMINAL VOLTAGE : ADJUSTABLE FROM 6VDC TO 120VDC. B) RATING : WITH CURRENT LIMIT ADJUSTABLE FROM 0-25 A.C) RIPPLE : <0.1% D) SHORT CIRCUIT PROTECTIONS AT OUTPUT OF THE BATTERY CHARGER BY MCCB. E) CIRCUIT BREAKER (2 POLE) AT THE OUTPUT OF THE BATTERY CHARGER F) PROTECTION AGAINST HIGH DC OUTPUT VOLTAGE SHALL BE PROVIDED. G) RATING: 100% CONTINUOUS AND SHALL BE						

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2492400059
DATE : 16.01.2024
REQ No : 1172300832
REQ TITLE : Power supply unit 1172300832
DELIVERY LOCATION : 0014 - G STORE SPAR&CHE
CLOSING DATE : 22.01.2024
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			ABLE TO BOOST CHARGE.H) COOLING METHOD: NATURAL CONVECTION.I) AUTOMATIC CURRENT LIMIT : 1 10%4. CONTROL & MONITORING:§ FOLLOWING ALARMS/INDICATIONS SHALL BE PROVIDED WITH THE BATTERYCHARGER.1. AC HEALTHY2. CHARGER ON3. CHA RGER FAULT4. OUTPUT VOLTAGE HIGH5. ALL THE METERS SHALL HAVE ACCURACY OF AT LEAST 1.0 CLASS.6. SHALL HAVE LIFTING HANDLE.§ ARRANGEME NT FOR DISPLAYING FOLLOWING PARAMETERS SHALL BE AVAILABLE.1. AC INPUT CURRENT2. AC INPUT VOLTAGE3. DC OUTPUT CURRENT4. DC OUTPUT VOL TAGE5. SPECIFICATION OF BATTERY CHARGER CABINET:A) CABINET SHALL BE FLOOR MOUNTING TYPE WITH WHEELS AND HANDLE FOR EASYTRANSPORTATIO N.B) EASY ACCESSIBILITY TO ALL THE PARTS OF THE BATTERY CHARGER FORMAINTENANCE AND REPLACEMET.C) PROTECTION CLASS OF THE CABINET SH						

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2492400059
DATE : 16.01.2024
REQ No : 1172300832
REQ TITLE : Power supply unit 1172300832
DELIVERY LOCATION : 0014 - G STORE SPAR&CHE
CLOSING DATE : 22.01.2024
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			ALL BE IP41 AT LEAST.6. SCOPE OF JOB:SUPPLY OF NEW PORTABLE BATTERY CHARGER.7. GENERAL CONDITIONS:A) MAINTENANCE AND OPERATION INSTR UCTION MANUALS AND SPARE PARTSREFERENCE LIST SHALL BE SUPPLIED.B) THE BATTERY CHARGER SHALL BE DESIGNEDFOR AMBIENT TEMPERATURE 50DEG CC) RELATIVE HUMIDITY:0 # 100%D) NOISE LEVEL @ 1 METER(TOLERANCE +/- 2 DBA): 60 DBAE) THE CHARGER TEST CERTIFICATE SHALL BE SUBMITT ED.F) TECHNICAL AND SPARE PARTS SUPPORT SHALL BE ENSURED FOR AT LEAST 15YEARS8. WARRANTY:A) THE CHARGER SHALL CARRY A WARRANTY FOR 2 YEARS.B) THE WARRANTY WILL TAKE EFFECT FROM THE DATE OF INSPECTION CLEARANCEBY DEWA.C)WHEN A DEFECT IS NOTICED ON THE EQUIPMENT DUR ING THE PERIOD OFWARRANTY, THE CONTRACTOR MUST RECTIFY THE DEFECT WITHIN A REASONABLEAMOUNT OF TIME FIXED BY DEWA WITH NO CLAIMS OR						

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2492400059
DATE : 16.01.2024
REQ No : 1172300832
REQ TITLE : Power supply unit 1172300832
DELIVERY LOCATION : 0014 - G STORE SPAR&CHE
CLOSING DATE : 22.01.2024
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			COMPENSATION.						
3	7000000013		PORTABLE BATTERY CHARGER - 10 AMPS 24V -240 VOLTS1. THE CHARGER SHALL BE MOBILE (WITH WHEELS AND STOPPER) AND DIGITALWITH BUILTIN AM METER AND VOLTMETERS FOR MEASURING AC, DC CURRENTS ANDVOLTAGES WHICH CAN BE USED DURING BATTERY CHARGING. THE CHARGER SHALL BEBUILT TO ABSORB SHOCKS DURING THE MOVEMENT FROM ONE PLACE TO OTHER. THECHARGER SHALL BE CAPABLE OF APPLYING HIGHER VOLTAGE FOR SEVERAL HOURS TOSPEED UP BATTERY CHARGING IN BOOST.2. INPUT:A) INPUT SUPPLY : AC 380V+ 10% , 3 PHASE, 50HZ + 5%, WITH SOFT STARTINGFACILITYB) OVERLOAD AND SHORT CIRCUIT PROTECTION AT INPUT OF THE BATTERY CHARGER: CIRCUIT BREAKER (3 POLE)C) SURGE SUPPRESSOR IN 3PHASE AC INP UT MAINS CIRCUIT FOR THE PROTECTIONAGAINST VOLTAGE SURGES.3. OUTPUT:A) NOMINAL	3	EA				

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2492400059
DATE : 16.01.2024
REQ No : 1172300832
REQ TITLE : Power supply unit 1172300832
DELIVERY LOCATION : 0014 - G STORE SPAR&CHE
CLOSING DATE : 22.01.2024
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			VOLTAGE : ADJUSTABLE FROM 24VDC TO 240VDC.B) RATING : WITH CURRENT LIMIT ADJUSTABLE FROM 0-10 A.C) RIPPLE : <0.1%D) SHORT CIRCUIT PROTECTIONS AT OUTPUT OF THE BATTERY CHARGER BY MCCB.E) CIRCUIT BREAKER (2 POLE) AT THE OUTPUT OF THE BATTERY CHARGERF) PROTECTION AGAINST HIGH DC OUTPUT VOLTAGE SHALL BE PROVIDED.G) RATING: 100% CONTINUOUS AND SHALL BE ABLE TO BOOST CHARGE.H) COOLING METHOD: NATURAL CONVECTION.I) AUTOMATIC CURRENT LIMIT : 110%4. CONTROL & MONITORING:§ FOLLOWING ALARMS/INDICATIONS SHALL BE PROVIDED WITH THE BATTERYCHARGER.1. AC HEALTHY2. CHARGER ON3. CHARGER FAULT4. OUTPUT VOLTAGE HIGH5. ALL THE METERS SHALL HAVE ACCURACY OF AT LEAST 1.0 CLASS.6. SHALL HAVE LIFTING HANDLE.§ ARRANGEMENT FOR DISPLAYING FOLLOWING PARAMETERS						

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2492400059
DATE : 16.01.2024
REQ No : 1172300832
REQ TITLE : Power supply unit 1172300832
DELIVERY LOCATION : 0014 - G STORE SPAR&CHE
CLOSING DATE : 22.01.2024
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			SHALL BE AVAILABLE.1. AC INPUT CURRENT2. AC INPUT VOLTAGE3. DC OUTPUT CURRENT4. DC OUTPUT VOLTAGE5. SPECIFICATION OF BATTERY CHARGER CABINET:A) CABINET SHALL BE FLOOR MOUNTING TYPE WITH WHEELS AND HANDLE FOR EASYTRANSPORTATION.B) EASY ACCESSIBILITY TO ALL THE PARTS OF THE BATTERY CHARGER FORMAINTENANCE AND REPLACEMENT.C) PROTECTION CLASS OF THE CABINET SHALL BE IP41 AT LEAST.6. SCOPE OF JOB:SUPPLY OF NEW PORTABLE BATTERY CHARGER.7. GENERAL CONDITIONS:A) MAINTENANCE AND OPERATION INSTRUCTIONS B) REFERENCE LIST SHALL BE SUPPLIED.C) THE BATTERY CHARGER SHALL BE DESIGNEDFOR AMBIENT TEMPERATURE 50DEGREE C) RELATIVE HUMIDITY:0 # 100%D) NOISE LEVEL @ 1 METER(TOLERANCE +/- 2 DBA): 60 DBAE) THE CHARGER TEST CERTIFICATE SHALL BE SUBMITTED.F) TECHNICAL AND SPARE PARTS SUPPORT						

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER : 2492400059
DATE : 16.01.2024
REQ No : 1172300832
REQ TITLE : Power supply unit 1172300832
DELIVERY LOCATION : 0014 - G STORE SPAR&CHE
CLOSING DATE : 22.01.2024
CLOSING TIME : 10:00:00

SL NO	ITEM CODE	SERVICE ID	DESCRIPTION	QTY	UOM	BRAND/ORIGIN	WARRANTY	UNIT PRICE	TOTAL PRICE
			SHALL BE ENSURED FOR AT LEAST 15YEARS8. WARRANTY:A) THE CHARGER SHALL CARRY A WARRANTY FOR 2 YEARS.B) THE WARRANTY WILL TAKE EFFECT FROM THE DATE OF INSPECTION CLEARANCEBY DEWA.C)WHEN A DEFECT IS NOTICED ON THE EQUIPMENT DU RING THE PERIOD OFWARRANTY, THE CONTRACTOR MUST RECTIFY THE DEFECT WITHIN A REASONABLEAMOUNT OF TIME FIXED BY DEWA WITH NO CLAIMS OR COMPENSATION.						

TOTAL AMOUNT IN WORDS:

TOTAL AMOUNT:

SPECIAL NOTES / INSTRUCTIONS:

Power supply unit

STANDARD TERMS & CONDITIONS

- 1) Prices should be 'DDP' delivery duty paid at DEWA stores.
- 2) Quotation to be submitted only in local currency U.A.E Dirhams

MATERIAL AND OR SERVICE PROVIDED TO DEWA SHOULD PREFERABLY BE ENERGY EFFICIENT AND ENVIRONMENT FRIENDLY.

REQUEST FOR QUOTATION LOCAL PURCHASE SECTION

RFQ NUMBER	: 2492400059
DATE	: 16.01.2024
REQ No	: 1172300832
REQ TITLE	: Power supply unit 1172300832
DELIVERY LOCATION	: 0014 - G STORE SPAR&CHE
CLOSING DATE	: 22.01.2024
CLOSING TIME	: 10:00:00

- 3) DEWA Standard payment terms is '30 days credit' from the date of acceptance of material
- 4) No DEWA staff or his or her relatives up to third degree should have ownership or partnership in your company, and your participation in DEWA tenders / RFQs should not constitute a Conflict or perceived Conflict of Interest.
- 5) The offered product and/ or services in the Quotation, shall be conforming and in accordance with DEWA Energy Management Policy & EnMS Manual.

SUPPLIER'S REMARKS :

SUPPLIER'S SIGNATURE AND STAMP